




Model Number: JM-FL133133-18-08

Spec: 133*133mm 8Ω 20W


这是一款应用于家庭影院系统、背景音乐系统、公共广播系统等重低音扬声器。磁路部分采用铁氧体磁路材料相结合设计，增强了磁通密度，提高产品声压特性，并改善了产品散热能力，同时大大提升了产品性价比。振动系统采用较轻的高耐疲劳度材质悬边+进口纸浆胴体，优化听觉效果，弹波采用高顺性材质，有效的降低失真，改善低频辅射特性。



LEAP Emulational Frequency Response




Frequency and impedance Response



specifications

DC Resistance	Revc	Ω	6.5	$\pm 7.5\%$	Energy Bandwidth product	EBP	$(1/Q_{es}).f_s$	145
Minimum impedance	Zmin	Ω	8	$\pm 7.5\%$	Moving Mass	Mms	g	13.399
Voice Coil inductance	Le	mH	53.11		Suspension Compliance	Cms	$\mu m/N$	344
Resonant Frequency	Fs	Hz	75.1	$\pm 20\%$	Effective Cone Diameter	SD	cm	93.31
Mechanical Q factor	Qms	-	3.111		Equivalent Volume	Vas	mL	4.133
Electrical Q factor	Qes	-	0.515		Motor Efficiency Factor	BL	T.M	8.942
Total Q facto	Qts	-	0.442		Voice Coil Former Material	VCfm	-	25.5
Ratio	Fs/Qts	-	169		Voice Coil Inner Diameter	VCd	mm	Kapton
Half Space Sensitivity @	1w/1m	dB	87.2 ± 2		Gap Height	Gh	mm	5
rated Noise Power(IEC 2685 18.1)	P	W	20		Maximum Linear Excursion	Xmax	mm	3.5
Test Spectrum Bandwidth	FO-20KHz		12dB/Oct		Ferrofluid Type	FF	N/A	Ferrite
					Transducer Size	-	-	133*133
	Transducer Mass	-		g				804

Mechanical 2D Drawing



Shenzhen Jiming Technology Co., Ltd
www.jmaxx.cn