


DC Resistance	Revc	Ω	5.2	$\pm 7.5\%$	Energy Bandwidth product	EBP	(1/Qes).fs	
Minimum impedance	Zmin	Ω	6	$\pm 7.5\%$	Moving Mass	Mms	g	
Voice Coil inductance	Le	mH			Suspension Compliance	Cms	um/N	
Resonant Frequency	Fs	Hz	1.0K	$\pm 20\%$	Effective Cone Diameter	SD	cm	
Mechanical Q factor	Qms	-			Equivalent Volume	Vas	mL	
Electrical Q factor	Qes	-			Motor Efficiency Factor	BL	T.M	
Total Q facto	Qts	-			Voice Coil Former Material	VCfm	-	ASV
Ratio	Fs/Qts	-			Voice Coil Inner Diameter	VCd	mm	25.5
Half Space Sensitivity @	1w/0.5m	dB	92 $\pm$ 2		Gap Height	Gh	mm	2
rated Noise Power(IEC 2685 18.1)	P	W	5		Maximum Linear Excursion	Xmax	mm	0.1
Test Spectrum Bandwidth	FO-20KHz		12dB/Oct		Ferrofluid Type	FF	N/A	NeFeB
					Transducer Size	-	-	54*71
					Transducer Mass	-	g	61.7



Shenzhen Jiming Technology Co., Ltd
www.jmaxx.cn