




Model Number: JM-AL032032-01-08
Spec: 32mm 8Ω 2W


这是一款应用于便携式数码音箱的高效率全频扬声器。支架采用高强度 ABS 材料，有利于磁通集中，减小漏磁。磁路部分采用两个钕磁，增强了磁通密度，提高产品声压特性，同时有效的减小产品体积和重量。振动系统采用较轻的高耐疲劳泡边材质悬边+进口纸浆胴体，优化听觉效果，弹波采用高顺性材质，有效的降低失真，改善低频辅射特性。



LEAP Emulational Frequency Response



Frequency and impedance Response



specifications

DC Resistance	Revc	Ω	3.6	±7.5%	Energy Bandwidth product	EBP	(1/Qes).fs	174.09
Minimum impedance	Zmin	Ω	4	±7.5%	Moving Mass	Mms	g	287.5601
Voice Coil inductance	Le	mH	3.88		Suspension Compliance	Cms	um/N	62.530
Resonant Frequency	Fs	Hz	375	±20%	Effective Cone Diameter	SD	cm	4.524
Mechanical Q factor	Qms	-	2.455		Equivalent Volume	Vas	mL	18.17
Electrical Q factor	Qes	-	2.154		Motor Efficiency Factor	BL	T.M	1.43
Total Q facto	Qts	-	1.147		Voice Coil Former Material	VCfm	-	ASV
Ratio	Fs/Qts	-	326.9		Voice Coil Inner Diameter	VCd	mm	13.28
Half Space Sensitivity @	1w/1m	dB	80.5±2		Gap Height	Gh	mm	1.5
rated Noise Power(IEC 2685 18.1)	P	W	2		Maximum Linear Excursion	Xmax	mm	1.265
Test Spectrum Bandwidth	FO-20KHz		12dB/Oct		Ferrofluid Type	FF	N/A	NeFeB
					Transducer Size	-	-	32*32
					Transducer Mass	-	g	19.1

Mechanical 2D Drawing

